

SMMSu / SHRMu VRF Indoor Unit MMD-UP0211BHP-UL—Concealed Duct



Submittal Data

Job Name _____ Location _____
Tag _____



A210775

SMMSu / SHRMu CONCEALED DUCT FEATURES

- R-410A Refrigerant
- Twelve sizes from 7,500 to 54,000 Btu/h
- Standard condensate pump with 24.3 in. lift capability
- Quiet operation, as low as 30 dBA
- Rear return configurable for bottom return
- Auto or manually set three fan speeds
- Five-year parts limited warranty

INDOOR UNIT MODEL		MMD-UP0211BHP-UL
PERFORMANCE		
Cooling Rated Capacity	Btu/h	21,000
Heating Rated Capacity	Btu/h	24,000
Fan Type (Qty)		Centrifugal (1)
External Static Pressure (ESP)	in. WG	0.6 (Factory default) 0.8 (Max)
Standard Airflow (H / M / L)	CFM	706 / 583 / 512
Sound Pressure (H / M / L)*	dBA	44 / 34 / 30
FILTER (Standard)		
Type		Washable
Quantity		2
MERV Corresponding Value		5
Dimensions (W x L x D)	in.	10-5/8 x 27-5/8 x 5/8
ELECTRICAL		
Power Supply	V/Ph/Hz	208-230/1/60
Power Consumption (Input)	kW	0.21
Full Load Amps (FLA)	A	1.78
Minimum Circuit Amps (MCA)	A	2.23
Maximum Overcurrent Protection (MOCP)	A	15.0

MOTOR		
Motor Type		DC
Motor Watts		150
PHYSICAL DATA		
Pipe Connection Size - Liquid	in.	3/8 (Flare)
Pipe Connection Size - Suction	in.	5/8 (Flare)
Pipe Connection Size - Drain (OD)	in.	1-1/4
Pipe Connection Size - Drain (ID)	in.	1
Refrigerant		R-410A
External Finish		Zinc Hot Dipped Steel Plate
Unit Width	in.	55-1/4
Unit Height	in.	10-7/8
Unit Depth	in.	29-5/8
Net Weight	lb	93


ACCESSORIES

- Wired Remote Controller (7-Day Programmable) RBC-AMS54E-UL / RBC-AWSU52-UL
- Simple Wired Remote Control RBC-AS41UL
- Remote Sensor TCB-TC41U-UL
- Auxiliary OA Flange TCB-FF151US-UL
- Zoning Duct Flange TCB-SF56C6BP-UL
- Filter Kit TCB-FW561DP-UL

* The actual values in an external operating environment are generally higher than the indicated values due to ambient noise.

DIMENSIONAL DRAWING

CONCEALED DUCT MMD-UP0211BHP-UL



All dimensions are shown in inches.



A210778