

In addition to having the smallest footprint of any Class CC, J or RK fuse solution, the Bussmann series Low-Peak CUBEFuse is the only product included in the UL Class CF. It's a current-limiting, dual-element, time-delay branch circuit fuse with Class J electrical performance. And it features industry-first plug-in capability for easier installation.

The finger-safe CUBEFuse is available in both indicating and non-indicating versions, with the indicating version featuring *easyID™* open fuse technology for faster troubleshooting and reduced downtime.

The CUBEFuse is easily applied with CUBEFuse holders, Compact Circuit Protector switches or the Compact Circuit Protector Base.



CUBEFuse catalog numbers (amps)

Indicating	Non-indicating	Indicating	Non-indicating
-	TCF1RN	TCF110	TCF110RN
-	TCF3RN	TCF125	TCF125RN
TCF6	TCF6RN	TCF150	TCF150RN
TCF10	TCF10RN	TCF175	TCF175RN
TCF15	TCF15RN	TCF200	TCF200RN
TCF17-1/2	TCF17-1/2RN	TCF225	TCF225RN
TCF20	TCF20RN	TCF250	TCF250RN
TCF25	TCF25RN	TCF300	TCF300RN
TCF30	TCF30RN	TCF350	TCF350RN
TCF35	TCF35RN	TCF400	TCF400RN
TCF40	TCF40RN		
TCF45	TCF45RN		
TCF50	TCF50RN		
TCF60	TCF60RN		
TCF70	TCF70RN		
TCF80	TCF80RN		
TCF90	TCF90RN		
TCF100	TCF100RN		

Volts:

- 600 Vac
- 300 Vdc

Amps:

- 6 to 400 A (indicating)
- 1 to 400 A (non-indicating)

Interrupting rating:

- 300 kA RMS Sym. (up to 100 A UL)
- 200 kA RMS Sym. (110 to 400 A UL)
- 200 kA RMS Sym. (Up to 100 A CSA®)
- 100 kA DC (up to 400 A UL and up to 100 A CSA)

Agency information:

- UL Listed Class CF fuse: Guide JDDZ, File E4273 (up to 400 A)
- CSA Certified fuse: Class 1422-02, File 053787_C_000 (up to 100 A)
- CE (100 A and below)
- RoHS Compliant



1 to 30 amps



35 to 60 amps



70 to 100 amps



110 to 225 amps



250 to 400 amps



We like using CUBEFuse products for their compact size, amperage range, finger-safe features, and ease of change-out.

The color scheme also stands out well so the bank of fuses is easy to locate in the cabinet.
-Ingersoll Production Systems