

2018 White-Rodgers Cooling Season Program

Qualifying Products

Model Number	Order Number	Description	Case Qty	UPC/ Bar Code
500RB 6T4VLC	063339	500RB Normally Open, Pilot-Operated Solenoid Valve	6	68134463392
500RB 7S5VLC	064038	500RB Normally Open, Pilot-Operated Solenoid Valve	12	681344640383
500RB 7T4VLC	064064	500RB Normally Open, Pilot-Operated Solenoid Valve	12	681344640642
540RA 12T7TVLC	046269	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344462695
540RA 12T7VLC	060397	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344603975
540RA 12T9VLC	060398	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344603982
540RA 16T9TVLC	046270	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	1	681344462701
540RA 16T9VLC	060399	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	1	681344603999
540RA 20T11TVLC	047953	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	1	681344479532
540RA 20T13TVLC	047954	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	4	681344479549
540RA 20T13VLC	060402	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	1	681344604026
540RA 8T4TVLC	058573	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344585738
540RA 8T5TVLC	046265	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344462657
540RA 8T5VLC	060392	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344603920
540RA 9T5TVLC	046266	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344462664
540RA 9T7TVLC	046268	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344462688
540RA 9T7VLC	060395	540RA Normally Open, Pilot-Operated, Diaphragm Solenoid Valve	12	681344603951
57T01-843	57T01-843	Trane Direct Replacement Single Stage Blower Time Delay Used for Postpurge on Trane Air Handlers. Contacts: Normally Open, 7 FLA, 36 LRA at 240 VAC, Pilot Duty: 25 VA at 24 VAC, On Delay: 2 Sec, Off Delay: 80 Sec. Replaces Trane Part Numbers C800924P01, RLY 2807	10	786710537585
8A18Z-2*	08A18Z002S1*	Evaporative Cooler Transformer Relay Control Panel, Part Of 21D28-6 Evaporative Cooler Package	6	786710353789
90-163*	90 163S1*	3 Pole Contactor, 24 VAC Coil, 30 Amp Contacts, 7.2 Ohms DC Resistance, 187 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710070105
90-164*	90 164S1*	3 Pole Contactor, 120 VAC Coil, 30 Amp Contacts, 180 Ohms DC Resistance, 37 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710070129
90-165*	90 165S1*	3 Pole Contactor, 208/240 VAC Coil, 30 Amp Contacts, 720 Ohms DC Resistance, 19 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710027666
90-170*	90 170S1*	3 Pole Contactor, 24 VAC Coil, 40 Amp Contacts With Dust Cover, 7.2 Ohms DC Resistance, 187 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710070198
90-171	90 171S1	3 Pole Contactor, 120 VAC Coil, 40 Amp Contacts With Dust Cover, 180 Ohms DC Resistance, 37 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710027680
90-172*	90 172S1*	3 Pole Contactor, 208/240 VAC Coil, 40 Amp Contacts With Dust Cover, 720 Ohms DC Resistance, 19 mA, 4.5 VA (Nominal), Maximum 52 VA (Inrush)	20	786710027697
90-244*	90 244S1*	2 Pole Contactor, 24 VAC Coil, 30 Amp Contacts, 11 Ohms DC Resistance, 250 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710070396
90-245*	90 245S1*	2 Pole Contactor, 120 VAC Coil, 30 Amp Contacts, 224 Ohms DC Resistance, 50 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710070426
90-246*	90 246S1*	2 Pole Contactor, 208/240 VAC Coil, 30 Amp Contacts, 997 Ohms DC Resistance, 25 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710027796
90-247*	90 247S1*	2 Pole Contactor, 24 VAC Coil, 40 Amp Contacts, 11 Ohms DC Resistance, 250 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710027802
90-248*	90 248S1*	2 Pole Contactor, 120 VAC Coil, 40 Amp Contacts, 224 Ohms DC Resistance, 50 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710027819
90-249*	90 249S1*	2 Pole Contactor, 208/240 VAC Coil, 40 Amp Contacts, 997 Ohms DC Resistance, 25 mA, 6 VA (Nominal), Maximum 32 VA (Inrush)	50	786710027826
9148	028032	T-Series THR Flange 1-1/8" X 1-1/8" ODM S/T	12	681344280329
9148-1	065125	T-Series TMR Flange 1-1/8" X 1-1/8" ODM S/T, (PS-370)	12	681344651259
9149	028030	T-Series THR Flange 1-1/8" X 1-1/8" ODM ANG	12	681344280305
9149-1	065124	T-Series TMR Flange 1-1/8" X 1-1/8" ODM ANG (PS-370)	12	681344651242
9150	028849	T-Series TIR Flange 7/8" ODF X 1-1/8" ODMS/T	12	681344288493
9151	027926	T-Series TIR Flange 7/8" ODF X 1-1/8" ODM ANG	12	681344279262
9152	027918	T-Series TER Flange 7/8ODFX1-1/8ODMS/T (PS-259)	16	681344279187
9153	027919	T-Series TER Flange 7/8ODFX1-1/8ODMANG (PS-259)	16	681344279194
935-106A	063241	T-Series 15FT3/8X1/2ODFANG	12	681344632418
935-106B	059382	T-Series 15FT3/8X1/2ODFANG	12	681344593825
94-388*	94 388S1*	1.5 Pole Contactor, 24 VAC Coil, 50/60 Hz, 30 Amp Contacts. Coil Data: 16.5 Ohms DC Resistance, 208 mA, 5 VA (Nominal), Maximum 20 VA (Inrush). Approximate Dimensions: 3-1/4" x 2" x 2 1/2"	50	786710028632
94-389*	94 389S1*	1.5 Pole Contactor, 120 VAC Coil, 50/60 Hz, 30 Amp Contacts. Coil Data: 420 Ohms DC Resistance, 42 mA, 5 VA (Nominal), Maximum 20 VA (Inrush). Approximate Dimensions: 3-1/4" x 2" x 2 1/2"	50	786710028649
94-394*	94 394S1*	1.5 Pole Contactor, 24 VAC Coil, 50/60 Hz, 40 Amp Contacts. Coil Data: 16.5 Ohms DC Resistance, 208 mA, 5 VA (Nominal), Maximum 20 VA (Inrush). Approximate Dimensions: 3-1/4" x 2" x 2 1/2"	50	786710036361
9761-2	027770	T-Series, TLE And ZZ Series Flange 1/2" X 7/8" ODF S/T	16	681344277701

* Product rebates will not be awarded for both the heating and cooling season program.
If the distributor is participating in both programs, overlapping product will fall under the cooling rebate.