

REPLACEMENT PARTS FOR UNIT HEATERS

MODEL UBX: STANDARD POWER VENT BLOWER TYPE
MODEL UBZ: SEPARATED-COMBUSTION BLOWER TYPE
MODEL UDX: STANDARD POWER VENT FAN TYPE
MODEL UDX: SEPARATED-COMBUSTION FAN TYPE



TABLE OF CONTENTS

WARRANTY 2
REFERENCES 2
SERIAL NUMBER..... 2
ELECTRICAL COMPONENTS..... 3
FAN AND MOTOR COMPONENTS 8
BLOWER COMPONENTS 9
CABINET COMPONENTS18
VENTER AND FLUE WRAPPER COMPONENTS......21
HEAT EXCHANGER AND BURNER ASSEMBLY COMPONENTS......24
VENTING AND COMBUSTION AIR KIT COMPONENTS (MODELS UDX AND UBZ)......27
ACCESSORIES/OPTIONS28

IMPORTANT

- 1. Always include complete model and serial number so that any specification change can be considered for parts replacement. It can save time and expense.
- 2. In keeping with our policy of continuous product improvement, we reserve the right to alter any information shown here. Specifications are subject to change without notice.
- 3. We reserve the right to substitute functional replacements.
- 4. Order by Part Number (PN) not by option designation.

BLOWER COMPONENTS—CONTINUED

Table 9. TEFC-Type Belt-Drive Blower Motor Assembly Components (Unit Sizes 150–400)																	
Item 1A: Motor					Item 3: Starter				Item 4: Starter Overload				Item 5: Contactor				
HP	Full Load Amps (FLA)	Manufacturer's Model	Frame Size	Shaft Size (Inches)	Service Factor	Power Factor	Efficiency	Voltage/Phase	PN	GE Model	PN	Min Amps	Max Amps	GE Model	PN	GE Model	
1/4	3.8	Regal Beloit C664	H56	5/8	1	—	—	120/1	CL00A310T-J	151146	RTA1-K	2.50	RTA1-K	151190	42AF35AF	119626	
	2.0				1.35			208/1	CL00A310T-L	151150	RTA1-J	2.70	RTA1-J	151189	42AF35AG	119627	
	1.9				1			240/1	CL00A310T-S	151147	RTA1-G	1.90					
	1.1	USMTR T14S2A	56			61.9		208/3	CL00A310T-L	151150		1.50	151184	42AF35AF	119626		
	0.5					68.5		240/3	CL00A310T-S	151147		0.40					
1/3	4.6	AOS-906L	N48	1/2	1	72.1%		480/3	CL00A310T-J	151146	RTA1-D	0.65	RTA1-D	151184	42AF35AG	119626	
	2.3					67.2		120/1	CL00A310T-L	151150	RTA1-J	4.00	RTA1-J	151189			
	2.4					—		208/1	CL00A310T-S	151147		1.80					
	1.2	AOS-H261	L48		1.15			240/1	CL00A310T-S	151147		1.00		RTA1-G	—		
	0.6				—			208/3	CL00A310T-L	151150	RTA1-G	1.50					
7.2	AOS-C613	J56	1.15					480/3	CL00A310T-J	151146		5.50	RTA1-M	151192	42AF35AF	119626	
3.5			—		120/1	CL00A310T-L		151150	RTA1-K	2.50	151190	42AF35AG	119627				
3.6					208/1	CL00A310T-S		151147		4.10	151189						
1/2	2.3	AOS-H274	H56	5/8	1	59.5		208/3	CL00A310T-L	151150	RTA1-J	2.70	RTA1-J	151189	42AF35AF	119626	
	2.0					76.4		240/3	CL00A310T-S	151147	1.80						
	1.0							480/3	CL00A310T-S	151146	0.65	151186	—				
	0.7	AOS-H276	J56		1.15			77.0%	575/3	105568	CL01A310T-J	151151	RTA1-P	151194	42AF35AF	119626	
	3/4	11.0	AOS-F353		F56	5/8		1	66	65.7%	120/1	CL00A310T-L	151150	RTA1-L	151191	42AF35AG	119627
5.4		208/1		115860						RTA1-L	6.30						
5.5		240/1		CL00A310T-S							151147	4.00					
2.0		AOS-H580	KA56	1	73.5			208/3	CL00A310T-L	151150	RTA1-J	2.70	RTA1-J	151189	42AF35AG	119627	
2.2					81.1%			240/3	CL00A310T-S	151147	1.80						
1.1	480/3							CL00A310T-S	151147	1.00	RTA1-G	151187	42AF35AF	119626			
1	0.8	AOS-H461	L56	5/8	1.15	78.3		82.0%	575/3	105569	CL00A310T-J	151146	RTA1-F	151186	—	42AF35AF	119626
	12.0	AOS-159105	120/1		CL01A310T-J	151151		RTA1-P	151194	42AF35AF	119626						
	6.2		208/1		CL00A310T-L	151150		RTA1-P	151194	16.00	RTA1-P	151194	42AF35AF	119626			
	6.0		240/1		CL00A310T-S	151147		5.50	RTA1-M	151192	8.50	RTA1-M	151192	42AF35AG	119627		
	1	3.3	WEG-00118E		D56	5/8		1	74.4	80.2%	208/3	CL00A310T-L	151150	RTA1-K	151190	42AF35AG	119627
3.1		240/3		CL00A310T-S						151147	2.50	RTA1-K	151190				
1.6		480/3		CL00A310T-S						151147	1.30	RTA1-H	151188	42AF35AF	119626		
1.4		AOS-H525	56	1.15	71.6			80.4%	575/3	105570	CL00A310T-J	151146	RTA1-G	151187	—	42AF35AF	119626
1.4		AOS-H525	56	1.15	80.4%		575/3	105570	CL00A310T-J	151146	RTA1-G	151187	—				

*Requires a starter. Consult the factory for a wiring diagram or serial number to determine the appropriate starter and overload.

*Requires a starter. Consult the factory for a wiring diagram or serial number to determine the appropriate starter and overload.