



Type		Connection Size Inches	Volume of DeSSicant cm ³	Overall Length mm		Solder Socket Depth mm	Diameter of Body mm	Shipping Weight kg
SAE Flare	ODF Solder			SAE Flare	ODF Solder			
C-052-HH	C-052-S-HH	1/4	82	120	108	9	62	0.34
C-082-HH	—	1/4	174	143	131	—	67	0.57
C-083-HH	C-083-S-HH	3/8		154	135	11		
C-162-HH	—	1/4	262	160	148	—	76	0.80
C-163-HH	C-163-S-HH	3/8		171	151	11		
C-164-HH	C-164-S-HH	1/2		177	154	13		
C-165-HH	C-165-S-HH	5/8		185	161	16		
C-303-HH	—	3/8	492	246	225	—	76	1.60
C-304-HH	C-304-S-HH	1/2		251	228	13		
C-305-HH	C-305-S-HH	5/8		259	234	16		
C-414-HH	—	1/2	672	251	230	—	89	2.00
C-415-HH	—	5/8		259	237	—		
—	C-417-S-HH	7/8		—	249	19		
RC-4864-HH	—	Replaceable Core	See Pages 24 and 25 for Replaceable Core Type Catch-All Specifications					
RC-10098-HH	—							