

Model: RKA5512EXD
Product Description

Type: Rotary Compressors
Application: HBP/AC - Air Conditioning
ProductDescription: R-22
Voltage/Frequency: 208-230V ~ 60Hz 200V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ARI (R-22)	230V ~ 60HZ	11700	2948	3428	1055	11.09	2.79	3.25	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	18.3°C (65°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 30
Weight Unit of Measure: LB
Displacement (cc): 16.273
Oil Type: Synthetic Alkylate
Viscosity (cSt): 53
Oil Charge (cc): 356

Electrical

Voltage Range (50 Hz): 180-220
Voltage Range (60 Hz): 197-254
Locked Rotor Amps (LRA): 26.3
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 4.8
Max. Continuous Current (MCC in Amps): 7.7
Motor Resistance (Ohm) - Main: 2.52

Motor Resistance (Ohm) - Start:
MotorType:

3.61
PSC

Overload Type:

Relay Type:

Agency Approval

cURus Recognized