



Fittings and Brackets




CAT. NO. AB-242
For use with either $\frac{3}{8}$ "
or $\frac{1}{2}$ " hanger rod




CAT. NO. AB252


CAT. NO.	A (IN.)	STD. CTN.
AB252 1	$3\frac{1}{8}$	10
AB252 2	$5\frac{1}{8}$	10
AB252 3	$7\frac{1}{8}$	10
AB252 4	$9\frac{1}{8}$	10




CAT. NO. AB253




CAT. NO. AB254 L




CAT. NO. AB254 R




CAT. NO. AB255




CAT. NO. AB257




CAT. NO. AB260 L




CAT. NO. AB260 R




CAT. NO. AB261




CAT. NO. AB263




CAT. NO. AB265




CAT. NO. AB274




CAT. NO. AB284 L




CAT. NO. AB284 R




CAT. NO. AB299




CAT. NO. N205




CAT. NO. N-219




CAT. NO. X201




CAT. NO. X204
Slot size is $\frac{9}{16}$ " x $1\frac{1}{2}$ "




CAT. NO. X207



CAT. NO. X208



CAT. NO. X289



CAT. NO. X299

Standard Dimensions

- Hole Spacing: $\frac{13}{16}$ " From End
- Hole Spacing: $1\frac{1}{8}$ " Centers
- Hole Size: $\frac{9}{16}$ " Diameter
- Material: $1\frac{1}{2}$ " Width
- Material: $\frac{1}{4}$ " Thick

Standard Finish – GoldGalv®, unless otherwise stated.
Add EG suffix for SilverGalv® Finish