

NOMENCLATURE IDENTIFICATION

ETAC2

Series Designation
ETAC2

-07

Cooling Capacity
07 - 7,000 BTU/H
09 - 9,000 BTU/H
12 - 12,000 BTU/H
15 - 15,000 BTU/H

HC

Model Type
HC - Cooling w/ Electric Heating
HP - Cooling & Heat Pump
w/ Backup Electric Heating

230V

Electrical Rating
230V - 208/230V 60Hz 1PH
265V - 265V 60Hz 1PH

A

Revision Level

-A

Environmental Protection
A - Standard Protection
CP - Corrosion Protection

COOLING W/ ELECTRIC HEATING

Model Number	ETAC2-07HC230VA-A	ETAC2-09HC230VA-A	ETAC2-12HC230VA-A	ETAC2-15HC230VA-A	ETAC2-07HC265VA-A	ETAC2-09HC265VA-A	ETAC2-12HC265VA-A	ETAC2-15HC265VA-A
Voltage Rating	208/230	208/230	208/230	208/230	265	265	265	265
Cooling BTU/H	7,000/7,200	9,200/9,400	11,600/11,800	14,200/14,500	7,200	9,400	11,800	14,500
Power Cord Selection Amp	15, 20	15, 20	15, 20 & 30	15, 20 & 30	15, 20	15, 20	15, 20 & 30	15, 20 & 30
Energy Efficiency Rating (EER)	13.0	12.1	11.6	10.4	13.0	12.1	11.6	10.4
Cooling Watts	535/550	760/775	1,000/1,015	1,365/1,390	550	775	1,015	1,390
Cooling Amps	2.9/2.7	3.9/3.7	5.1/4.9	6.7/6.2	2.4	3.3	4.2	5.4
CFM Low/Hi	282/312	294/329	306/341	306/341	282/312	294/329	306/341	306/341
Dehumidification (Pints/Hr)	1.69	2.11	2.75	3.17	1.69	2.11	2.75	3.17
Weight (Net/Ship)	104.5/124.3	113.3/133.1	117.0/137.5	118.8/138.6	105.6/125.4	113.3/133.1	116.6/136.4	118.8/138.6

COOLING & HEAT PUMP W/ BACKUP ELECTRIC HEATING

Model Number	ETAC2-07HP230VA-A	ETAC2-09HP230VA-A	ETAC2-12HP230VA-A	ETAC2-15HP230VA-A	ETAC2-07HP265VA-A	ETAC2-09HP265VA-A	ETAC2-12HP265VA-A	ETAC2-15HP265VA-A
Voltage Rating	208/230	208/230	208/230	208/230	265	265	265	265
Cooling BTU/H	7,000/7,200	9,200/9,400	11,600/11,800	14,200/14,500	7,200	9,400	11,800	14,500
Reverse Cycle BTU/H	5,800/6,000	8,100/8,300	10,400/10,600	13,000/13,300	6,000	8,300	10,600	13,300
Power Cord Selection Amp	15, 20	15, 20	15, 20 & 30	15, 20 & 30	15, 20	15, 20	15, 20 & 30	15, 20 & 30
Energy Efficiency Rating (EER)	13.0	12.1	11.6	10.4	13.0	12.1	11.6	10.4
COP	3.6/3.6	3.5/3.5	3.4/3.4	3.1/3.1	3.6	3.5	3.4	3.1
Cooling Watts	535/550	760/775	1,000/1,015	1,365/1,390	550	775	1,015	1,390
Cooling Amps	2.9/2.7	3.9/3.7	5.1/4.9	6.7/6.2	2.4	3.3	4.2	5.4
Reverse Cycle Heating Watts	470/485	675/695	895/910	1,225/1,255	485	695	910	1,255
Reverse Cycle Heating Amps	2.6/2.4	3.4/3.2	4.7/4.2	6.7/6.2	2.2	3.1	3.7	5.2
CFM Low/Hi	282/312	294/329	306/341	306/341	282/312	294/329	306/341	306/341
Dehumidification (Pints/Hr)	1.69	2.11	2.75	3.17	1.69	2.11	2.75	3.17
Weight (Net/Ship)	111.1/130.9	117.7/137.5	119.9/139.7	122.1/141.9	110.1/129.8	117.7/137.5	117.7/137.5	119.9/141.9

POWER CORDS

Model Number	E2CORD-230V15A	E2CORD-230V20A	E2CORD-230V30A	E2CORD-265V15A	E2CORD-265V20A	E2CORD-265V30A
Voltage Rating	208/230	208/230	208/230	265	265	265
Electric Heating BTU/H	6,800/8,300	9,600/11,700	13,900/17,000	8,300	11,700	17,000
Heater KW	2.45	3.45	5.0	2.45	3.45	5.0
Electric Heating Watts	2,003/2,450	2,821/3,450	4,089/5,000	2,450	3,450	5,000
Electric Heating Amps	9.7/10.7	13.6/15.0	19.7/21.8	9.3	13.1	18.9
Minimum Circuit Ampacity	14	19	28	12	17	24
Receptacles Type	Tandem	Perpendicular	Large Tandem	265V 15 Amp	265V 20 Amp	265V 30 Amp
NEMA Number	6-15P	6-20P	6-30P	7-15P	7-20P	7-30P
Breaker Size	15	20	30	15	20	30

Specifications are subject to change. Manufacturer reserves the right to discontinue or modify specification or design without notice or without incurring obligation.
All rights reserved. ©2016

