



Model Number	Item Number (Bill of Material)	Volt/Hz/Ph	HP	Motor Type	Starting Torque	Rating (Btu/h)	Connection Size (in)		Wt (lbs)
							Suction	Discharge	
R22 Compressor Reciprocating (model begins with “A”) and Rotary (model begins with “R”) (continued)									
High Temperature and A/C Rated @ 45°F (continued)									
AVB5549EXN	AV178ET-041-J7	208-230/60/1	4	PSC	Normal	49,000	7/8 ODF	1/2 ODF	92
AGA5553EXN	AG122ET-016-J7	208-230/60/1	4 1/2	PSC	Normal	54,000	7/8 ODF RL	1/2 ODF	103
AGA5553EXN	AG122ET-003-J7	208-230/60/1	4 1/2	PSC	Normal	54,000	7/8 ODF	1/2 ODF	103
AGA5553EXT	AG122RT-016-J7	200-230/60/3	4 1/2	3PH	3 PH	54,000	7/8 ODF RL	1/2 ODF	97
AGA5553EXT	AG122RT-003-J7	200-230/60/3	4 1/2	3 PH	3 PH	54,000	7/8 ODF	1/2 ODF	97
AGC5553EXG	AG122UT-003-J7	460/60/3	4 1/2	3 PH	3 PH	54,000	7/8 ODF	1/2 ODF	98
AGA5553EXH	AG122VT-004-J7	575/60/3	4	3 PH	3 PH	52,000	7/8 ODF	1/2 ODF	98
AVB5558EXT	AV190RT-045-J7	200-230/60/3	4 3/4	3 PH	3 PH	57,000	7/8 ODF	1/2 ODF	89
AVB5558EXN	AV190ET-047-J7	208-230/60	4 3/4	PSC	Normal	57,500	7/8 ODF	1/2 ODF	88
AVB5558EXG	AV190TT-045-J7	460/60/3	5	3 PH	3 PH	57,000	7/8 ODF	1/2 ODF	82
AVB5558EXH	AV190VT-045-J7	575/60/3	5	3 PH	3 PH	57,000	7/8 ODF	1/2 ODF	82
AGA5561EXH	AG133VT-003-J7	575/60/3	5	3 PH	3 PH	61,000	7/8 ODF	1/2 ODF	99
AGA5561EXN	AG133ET-001-J7	208-230/60/1	5	PSC	Normal	61,000	7/8 ODF	1/2 ODF	107
AGA5561EXT	AG133RT-003-J7	200-230/60/3	5	3 PH	3 PH	61,000	7/8 ODF	1/2 ODF	107
AGC5561EXG	AG133UT-003-J7	460/60/3	5	3 PH	3 PH	61,000	7/8 ODF	1/2 ODF	99
AGB5568EXH	AG144XT-003-J7	575/60/3	5	3 PH	3 PH	67,500	7/8 ODF	1/2 ODF	102
AGA5568EXN	AG144ET-002-J7	208-230/60/1	5	PSC	Normal	68,000	7/8 ODF	1/2 ODF	112
AGA5568EXN	AG144ET-015-J7	208-230/60/1	5 1/2	PSC	Normal	68,000	7/8 ODF RL	1/2 ODF	112
AGA5568EXT	AG144RT-014-J7	200-230/60/3	5 1/2	3PH	3 PH	68,000	7/8 ODF RL	1/2 ODF	101
AGA5568EXT	AG144RT-001-J7	200-230/60/3	5 1/2	3 PH	3 PH	68,000	7/8 ODF	1/2 ODF	101
AGC5568EXG	AG144UT-001-J7	460/60/3	5 1/2	3 PH	3 PH	68,000	7/8 ODF	1/2 ODF	102
AGA5573EXG	AG188UT-001-J7	460/60/3	6	3 PH	3 PH	72,500	7/8 ODF	1/2 ODF	110
AGA5573EXT	AG188RT-001-J7	200-230/60/3	6	3 PH	3 PH	72,500	7/8 ODF	1/2 ODF	110
R22 Compressor Reciprocating									
Commercial Temperature Rated @ 20°F									
AKA9428EXA	AK164AT-037-J7	115/60/1	1/3	CSIR	High	2,800	1/2 ODF	3/8 ODF	40
AKA9428EXA	AK164AT-038-J7	115/60/1	1/3	CSIR	High	2,800	1/2 SAE	1/4 ODF	40
AKA9428EXD	AK164ET-037-J7	208-230/60/1	1/3	CSIR	High	2,800	1/2 ODF	3/8 ODF	41
AKA9428EXD	AK164ET-038-J7	208-230/60/1	1/3	CSIR	High	2,800	1/2 SAE	1/4 ODF	41
AKA9442EXA	AK165AT-037-J7	115/60/1	1/2	CSIR	High	4,200	1/2 ODF	3/8 ODF	40
AKA9442EXA	AK165AT-038-J7	115/60/1	1/2	CSIR	High	4,200	1/2 SAE	1/4 ODF	40
AKA9442EXD	AK165ET-037-J7	208-230/60/1	1/2	CSR	High	4,200	1/2 ODF	3/8 ODF	43
AKA9442EXD	AK165ET-038-J7	208-230/60/1	1/2	CSR	High	4,200	1/2 SAE	1/4 ODF	43
AKA9455EXD	AK167ET-037-J7	208-230/60/1	3/4	CSR	High	5,500	1/2 ODF	3/8 ODF	43
AKA9455EXD	AK167ET-038-J7	208-230/60/1	3/4	CSR	High	5,500	1/2 SAE	1/4 ODF	43
AKA9462EXD	AK166ET-037-J7	208-230/60/1	3/4	CSR	High	6,200	1/2 ODF	3/8 ODF	43
AKA9462EXD	AK166ET-038-J7	208-230/60/1	3/4	CSR	High	6,200	1/2 SAE	1/4 ODF	43
AJA9484EXD	AJ801ET-418-J7	208-230/60/1	1	CSR	High	8,400	1/2 ODF	5/16 ODF	54
AJA9484EXD	AJ801ET-441-J7	208-230/60/1	1	CSR	High	8,400	5/8 SAE	5/16 ODF	54
AJA9484EXD	AJ801ET-431-J7	208-230/60/1	1	CSR	High	8,400	1/2 ODF	5/16 ODF	54
AJA9484EXD	AJ801ET-446-J7	208-230/60/1	1	CSR	High	8,400	1/2 ODF	3/8 ODF	54
R22/R407C Compressor Reciprocating									
High Temperature and A/C Rated @ 45°F									
AWG5520WXG	AW703VT-124-J7	460/60/3	1 3/4	3 PH	3 PH	20,000	3/4 ODF RL	3/8 ODF	70
AWG5520WXN	AW703HT-099-J7	208-230/60/1	1 3/4	PSC	Normal	20,200	3/4 ODF	7/16 ODF	65
AWG5520WXN	AW703HT-111-J7	208-230/60/1	1 3/4	PSC	Normal	20,200	1 1/4 RL	7/16 ODF	65
AWG5520WXT	AW703ST-120-J7	200-230/60/3	1 3/4	3 PH	3 PH	20,000	3/4 ODF	3/8 ODF	62
AWG5520WXT	AW703ST-121-J7	200-230/60/3	1 3/4	3 PH	3 PH	20,000	3/4 ODF RL	3/8 ODF	62
AWG5524WXN	AW705GT-099-J7	208-230/60/1	2	PSC	Normal	24,200	3/4 ODF	7/16 ODF	60
AWG5524WXT	AW705ST-120-J7	200-230/60/3	2	3 PH	3 PH	23,600	3/4 ODF	3/8 ODF	60
AWG5530WXN	AW707HT-099-J7	208-230/60/1	2 1/2	PSC	Normal	30,200	3/4 ODF	7/16 ODF	63
AWG5530WXT	AW707ST-120-J7	200-230/60/3	2 1/2	3PH	3 PH	28,900	3/4 ODF	3/8 ODF	63
AVA5538WXG	AV201UT-013-J7	460/60/3	3	3 PH	3 PH	38,400	7/8 ODF	1/2 ODF	82

RL = Roto Lock