

Floor Console Heat Pump Ductless System

Indoor Model: 45MBFAQ16XA3



Job Data:

Tag #:

Date:

Location:

Carrier#:

Turn to the experts



INDOOR STANDARD FEATURES


- Modes: Cool, Heat, Dry, Fan, Auto
- Four fan speeds
- Sleep Mode
- Turbo Mode
- Dual air outlets with wider vents for optimal airflow
- Follow Me (senses temperature at handheld remote)
- Auto-Restart function
- Quiet indoor operation
- Anti-corrosive fin coating

RESIDENTIAL APPLICATION LIMITED WARRANTY*

- Ten (10) years if properly registered within ninety (90) days after original installation, parts are warranted to the original purchaser for a period of ten (10) years. Otherwise, parts warranty is five (5) years.

NOTE: Images for illustration purposes only. Actual models may be slightly different.

45MBFAQ16XA3			
System	Indoor Model #		45MBFAQ16XA3
	Indoor Size		16000
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208-230/1/60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	3
Operating Range	Cooling Indoor DB Min - Max	°F(°C)	60~90 (16~32)
	Heating Indoor DB Min - Max	°F(°C)	32~86 (0~30)
Indoor Coil	Face Area	Sq. Ft.	2.24
	No. Rows		2
	Fins per inch		20
	Circuits		2
Indoor Unit	Number of Fan Speeds		1100/1000/900
	Airflow (highest to lowest)	CFM	500.31 / 441.45 / 382.59 / 323.73 / 206.01
	Sound Pressure (highest to lowest)	dB(A)	47/43.5/40.5/30.5/25.5
	Moisture Removal	L/h	2.18
	Air Throw Data	ft(m)	19.6(6)
Dimensions	Height	in (mm)	24.45(621)
	Width	in (mm)	31.26(794)
	Depth	in (mm)	7.87(200)
	Net Weight	lbs (kg)	32.85(14.9)
	Shipping Height	in (mm)	28.31(719)
	Shipping Width	in (mm)	34.06(865)
	Shipping Depth	in (mm)	11.02(280)
	Shipping Net Weight	lbs (kg)	41.89(19)
CONTROLS			
Standard	Wireless Remote Controller (°F/°C Convertible)		
Optional	Wired Remote Control 7 Day Programmable		KSACN1401AAA
	Wired Remote Control with Timer Function		KSACN1201AAA
	Wi-Fi™ Kit High Wall		KSAIF0701AAA
	24V Mini Interface		KSAIC0601230



INDOOR UNIT DIMENSIONS				
Capacity	Unit	W	D	H
9K ~ 18K	mm	794	200	621
	inch	31.26	7.87	24.45



Puron Advance™



Puron Advance™