

Loaded Clamp Meters

SC620, SC640, SC660

Top-of-the-Line Meters Have it All

Packed with more features and measurements than any clamp meter in the HVACR industry, the loaded SC600 series features lead storage, a swivel head, test lead holder for safer testing, and a heavy duty magnetic strap.

- Top-of-the-line meter
- Swivel-head clamp
- Magnetic ctrap
- Lead storage
- Dual display
- Clamp test-lead holder
- Frequency via leads & clamps
- Dial backlight (SC640 & 660)
- Jaw flashlight (SC640 & 660)
- LCD backlight (SC640 & 660)
- Phase rotation (SC660)
- Dual temperature delta T (SC660)
- Job Link compatible (SC660)

Included

- Wrap tab type K thermocouple - ATB1
- Deluxe silicone lead set with gold plated tips and removable sheath - ADLS2
- Short alligator lead extensions - ASA2
- Padded case - ANC7
- 9V battery
- Velcro strap



SC660



SC620



SC640



SC660

SC620	SC640	SC660	Function
●	●	●	Volts AC/DC
		●	Job Link® System
		●	Dual Temp Delta T
		●	Phase Rotation
	●	●	True RMS
	●	●	Inrush
●	●	●	Swivel Clamp
●	●	●	Magnetic Strap
●	●	●	Probe Storage
●	●	●	Dual Display
●	●	●	Temperature °F/ °C
●	●	●	Capacitance
●	●	●	Duty Cycle %
●	●	●	400 Amps AC
●	●	●	Microamps DC
●	●	●	Frequency via Leads/Clamp
●	●	●	Non Contact Voltage
●	●	●	50 Mega Ohm with 0.1 Resolution
●	●	●	Continuity
●	●	●	Diode Test
●	●	●	Hold
●	●	●	Clamp Probe Holder
	●	●	Dial Backlight
	●	●	Clamp Jaw Light
	●	●	LCD Backlight
●	●	●	Low Battery Indicator
	●	●	Battery: 9V, 100 hrs
●			Battery: 9V, 200 hrs
●	●	●	Compliance with UL 3rd Edition

