



# P32 Series Sensitive Pressure Switch Catalog Page

LIT-1927195

2020-04-22




## Description

This differential pressure switch is used to sense pressure/air flow in ducts.

Refer to the *P32 Series Sensitive Differential Pressure Switch Product Bulletin (LIT-125435)* for important product application information.

**Figure 1: P28 Action Diagram**



## Features

- easy-to-read setpoint scale
- versatile mounting options

## Applications

- pressure/air flow proving with electric duct heaters, humidifiers, and other equipment
- maximum pressure/air flow control for variable volume systems

P32AC, P32AF

- reheat duct powered systems
- clogged filter detection
- detection of icing of air conditioning coils and initiation of defrost cycle
- sensitive pressure settings





- dust-tight snap switch

## Repair Information

If the P32 Series Sensitive Pressure Switch fails to operate within its specifications, replace the unit. For a replacement switch, contact the nearest Johnson Controls® representative.

## Selection Chart

**Table 1: Selection Chart**

Product Code Number	Ambient Temperature Min./Max.	Connector	Maximum Overpressure psig (kPa) <sup>1</sup>	Contact Action	Range in. WC(kPa)	Sensitivity at Min.Setpoint in. WC (kPa)	Setpoint	Scale Plate	Mounting Bracket (Included)
P32AC-1C	-40°F (-40°C) min. 167°F (75°C) max.	High Pressure connectors are metal 1/8 in. internal NPT inside, 1/2 in. NPSM outside for mounting	1 (6.895)	Single-Pole Double-Throw (SPDT)	0.15 to 12 (0.037 to 2.99)	0.07 (0.017)	Adjustable	Yes	L  BKT182-1
P32AC-2C <sup>2</sup>									U  BKT229-1
P32AF-1C		Low pressure connectors are molded, 1/8 in. internal NPT			0.025 (0.006)	L  BKT182-1			
P32AF-2C <sup>2</sup>						U  BKT229-1			

<sup>1</sup> Maximum overpressure at either connection

<sup>2</sup> Supplied with 1/4 in. compression fitting, 4 in. extension tube, two mounting screws, and O-gasket (angle barbed fitting installed)

## Accessories

The switch can be mounted directly or with the supplied mounting bracket.

Product Code Number	Description
FTG18A-600R	Remote Mounting Kit: 4 in. flanged sensing tube, two barbed fittings, two No. 10 screws, and a gasket

## P32 Series Sensitive Pressure Switch Technical Specifications

**Table 2: Electrical Ratings**

Motor Ratings VAC	120	208	240
<b>Type P32AC (Standard Differential, 1/2 hp)</b>			
AC Full Load A	9.8	5.65	4.9
AC Locked Rotor A	58.8	33.9	29.4
Non-Inductive or Resistive Load	15 A, 24 to 277 VAC		
Pilot Duty	125 VA, 24 VAC; 360 VA, 120 to 277 VAC		
<b>Type P32AF (Close Differential, 1/4 hp)</b>			
AC Full Load A	5.8	3.3	2.9
AC Locked Rotor A	34.8	19.8	17.4
Non-Inductive or Resistive Load	10 A, 24 to 277 VAC		
Pilot Duty	125 VA, 24 VAC; 360 VA, 120 to 277 VAC		

## Product warranty

This product is covered by a limited warranty, details of which can be found at [www.johnsoncontrols.com/buildingswarranty](http://www.johnsoncontrols.com/buildingswarranty).

## Single point of contact

APAC	Europe	NA/SA
JOHNSON CONTROLS C/O CONTROLS PRODUCT MANAGEMENT NO. 32 CHANGJIANG RD NEW DISTRICT WUXI JIANGSU PROVINCE 214028 CHINA	JOHNSON CONTROLS WESTENDHOF 3 45143 ESSEN GERMANY	JOHNSON CONTROLS 507 E MICHIGAN ST MILWAUKEE WI 53202 USA

## Contact information

Contact your local branch office:  
[www.johnsoncontrols.com/locations](http://www.johnsoncontrols.com/locations)

Contact Johnson Controls:  
[www.johnsoncontrols.com/contact-us](http://www.johnsoncontrols.com/contact-us)