

Tool Totes

- Constructed of rugged, 600 x 300 denier polyester to resist wear and tear on the jobsite
- 2" (51 mm) wide polypropylene padded carrying handles with comfortable leather wrap
- Water-resistant to avoid the build-up of mold and mildew
- Exterior pockets hold a variety of tools and a mobile phone
- Multiple interior pockets and a large interior compartment for a wide assortment of tools and supplies (only with Cat. Nos. 58888 and Cat. No. 58890)
- Durable molded bottom with drain holes to prevent water retention
- Contoured, padded, slip-resistant shoulder strap for hands-free mobility (included with Cat Nos. 58888 and Cat. No. 58890)
- Heavy-duty chain tape thong (Cat. No. 58890 only)
- Made in USA with global components



58890

Cat. No.	Number of Pockets	Chain Tape Thong	Shoulder Strap	Overall Length	Overall Height	Overall Width
58886*	7	No	No	15.5" (393.7 mm)	10" (254.0 mm)	7.5" (190.5 mm)
58888	12	No	Yes	15.5" (393.7 mm)	10" (254.0 mm)	7.5" (190.5 mm)
58890	17	Yes	Yes	15.5" (393.7 mm)	10" (254.0 mm)	7.5" (190.5 mm)

*Optional shoulder strap (Cat. No. 58889) available.

Ten-Compartment Drawstring Bag

- 12 oz (340.2 g) olive canvas
- 10 compartments to hold small parts
- Drawstring for easy closing
- Made in USA with global components



5151

Cat. No.	Overall Height	Diameter	Weight
5151	6" (152.4 mm)	11" (279.4 mm)	0.40 lb (0.18 kg)

Leather Tote Bag

- Rugged tool bag made of extra-heavy leather
- Stitched and riveted construction
- Reinforced ends
- Double-ply bottom with steel studs
- Made in USA with global components



5115

Cat. No.	Overall Length	Overall Height	Overall Width
5115	15" (381.0 mm)	7" (177.8 mm)	6.5" (165.1 mm)

Deluxe Leather Bags

- Rugged tool bag made of extra-heavy leather
- Removable padded shoulder strap
- Three-ply bottom with steel studs
- Retaining straps extend around bag for extra support
- Made in USA with global components



5108-18

Cat. No.	Overall Length	Overall Height	Overall Width
5108-18	18" (457.2 mm)	8" (203.2 mm)	7" (177.8 mm)
5108-20	20" (508.0 mm)	8" (203.2 mm)	7" (177.8 mm)
5108-24	24" (609.6 mm)	8" (203.2 mm)	7" (177.8 mm)