

# Pulling grips

## Pulling grips catalog numbering system

Junior duty, light duty, medium duty, heavy duty,  
multi-weave & slack weave

## Pulling grips

**Pulling grips**  
**sample number:**  
**SKR40052**

| <b>SKR 400 52</b>                             |                                |                           |
|-----------------------------------------------|--------------------------------|---------------------------|
| <b>Grip type</b>                              | <b>Cord diameter reference</b> |                           |
| <b>LPJ</b> = Junior duty, flexible eye        | <b>25</b> = .25-.36"           | <b>200</b> = 2.00-2.49"   |
| <b>LP</b> = Light duty, flexible eye          | <b>37</b> = .37-.49"           | <b>250</b> = 2.50-2.99"   |
| <b>MP</b> = Medium duty, flexible eye         | <b>50</b> = .50-.61"           | <b>300</b> = 3.00-3.49"   |
| <b>PH</b> = Heavy duty, rotating eye          | <b>62</b> = .62-.74"           | <b>350</b> = 3.50-3.99"aa |
| <b>PMR</b> = Multi weave, rotating eye        | <b>75</b> = .75-.99"           | <b>400</b> = 4.00-4.49"   |
| <b>PMF</b> = Multi weave, flexible eye        | <b>100</b> = 1.00-1.25"        | <b>450</b> = 4.50-4.99"   |
| <b>SKT</b> = Slack, double weave, closed mesh | <b>125</b> = 1.25-1.49"        | <b>500</b> = 5.00-5.99"   |
| <b>SKTL</b> = Slack, double weave, split lace | <b>150</b> = 1.50-1.74"        | <b>600</b> = 6.00-6.99"   |
| <b>SKR</b> = Slack, single weave, split rod   | <b>175</b> = 1.75-1.99"        |                           |
| <b>Bale length</b>                            |                                |                           |
| <b>11</b> = 11"                               | <b>30</b> = 30"                |                           |
| <b>12</b> = 13"                               | <b>32</b> = 32" or 33"         |                           |
| <b>13</b> = 14"                               | <b>33</b> = 33"                |                           |
| <b>14</b> = 14" or 15"                        | <b>34</b> = 34"                |                           |
| <b>15</b> = 16"                               | <b>35</b> = 36"                |                           |
| <b>16</b> = 16" or 17"                        | <b>36</b> = 36"                |                           |
| <b>17</b> = 18"                               | <b>38</b> = 38"                |                           |
| <b>18</b> = 19"                               | <b>39</b> = 39"                |                           |
| <b>19</b> = 20"                               | <b>41</b> = 41"                |                           |
| <b>20</b> = 20" or 21"                        | <b>42</b> = 42"                |                           |
| <b>21</b> = 21" or 22"                        | <b>52</b> = 52"                |                           |
| <b>23</b> = 24" or 25"                        | <b>54</b> = 54"                |                           |
| <b>24</b> = 24"                               | <b>56</b> = 56"                |                           |
| <b>25</b> = 25" or 26"                        | <b>58</b> = 58"                |                           |
| <b>26</b> = 26" or 27"                        | <b>60</b> = 60"                |                           |
| <b>27</b> = 27" or 28"                        | <b>66</b> = 66"                |                           |
| <b>28</b> = 28"                               |                                |                           |



## Junior duty

### Product description

Flexible eye

### Features & applications

- Single weave variable mesh automatically adjusts its grip to the load providing non-slip pulling and protects cable insulation from damage
- They are woven from tinned-bronze wire to provide superior corrosion resistance and are available in single eye and locking bale configurations
- Junior duty series grips are indispensable tools for electricians with small job requirements
- Used in industrial plants, commercial buildings, utility work and light duty underground transmission line stringing
- Junior pulling grips designed for pulling insulated building wire through conduit where pulling tensions are low and to connect a bundle of insulated building wire to a pulling tape



LPJ62

### Flexible eye

| Cord diameter            | Mesh length   | Approx. break strength† | Catalog no.* |  |
|--------------------------|---------------|-------------------------|--------------|-------------------------------------------------------------------------------------|
| 0.25-0.36" (3.4-9.1mm)   | 5" (127.0mm)  | 1,700 lbs.              | □ LPJ25      | •                                                                                   |
| 0.37-0.49" (9.4-12.4mm)  | 7" (177.8mm)  | 1,700 lbs.              | □ LPJ37      | •                                                                                   |
| 0.50-0.61" (12.7-15.5mm) | 8" (203.2mm)  | 1,700 lbs.              | □ LPJ50      | •                                                                                   |
| 0.62-0.74" (15.7-19.0mm) | 10" (254.0mm) | 2,800 lbs.              | □ LPJ62      | •                                                                                   |
| 0.75-0.99" (19.1-25.1mm) | 10" (254.0mm) | 4,100 lbs.              | □ LPJ75      | •                                                                                   |
| 1.00-1.25" (25.4-31.8mm) | 12" (304.8mm) | 4,100 lbs.              | □ LPJ100     | •                                                                                   |

\*Contact the factory for stainless steel support grips.

† To determine workload safety factor, divide approximate break strength by 10. See page N-34 for strength information. Consult factory for price and availability.

**Compliances, specifications and availability are subject to change without notice.**



Indicates NAFTA compliant - Page Q-30