

Hydronic Fan Coils



CFFWA

CFFWA - The Universal Mount Fan Coil provides the greatest flexibility in satisfying your heating and cooling needs. The CFFWA may be installed on the floor, low on the wall, or horizontally on the ceiling, without internal modification. The unique and popular design style is available in capacities of 12,000 - 60,000 BTU/h. It is also available in 4-pipe configurations with model number **CFFWA4P**.



MHWW

MHWW - These Hi-Wall Fan Coils are specifically designed for unobtrusive, quiet operation in smaller zone applications. The MHWW provides a seamless appliance appearance in either residential or commercial application. These Hi-Wall mounted units are available in 9,000 to 36,000 BTU/h, 208/230V and 120V capacities. These units include washable air filters, a remote, and ductless mounting.



MHQWW

MHQWW - This latest model Hi-Wall gives our classic MHWW a modern, sleek appearance that lends itself to a more contemporary design. These ductless Hi-Wall mounted units are available in 9,000 to 36,000 BTU/h and 208/230V and 120V capacities. The unit includes a wireless infrared remote controller, wall mounted receiver, and washable filters. The unit is also capable of operating on any 24 volt thermostat.



CWA

CWA2 - A traditional, central - ducted type air handler. This vertical or horizontal air handler can be tied into the ductwork of the existing heating or cooling system. This configuration also lends itself to add on where additional cooling load may be required. Available in 18,000 to 60,000 BTU/h and 208/230V or 120V capacities. 5kW - 20kW electric heat available in 2-pipe models. It is also available as a 4-pipe with model number **CWA4**.