


PLUS II™ 3/8" HEAVY DUTY COMBINATION CHARGING/VACUUM HOSE

Pulls a vacuum much faster than the 1/4" hose.

- Operating temperature -22° to 176°F (- 30° to 80°C)
- 3000 psi (207 bar) minimum burst, 600 psi (41 bar) maximum working pressure
- Minimum bend radius: 8" (203 mm)
- **Vacuum rated to 20 microns**
- Made in the USA 




Replacement parts	
UPC#	Description
19020	1/4" Replacement gasket (10 pak)
19011	3/8" Replacement gasket (10 pak)
19302	"Adjust-a-Valve" opener (10 pak)

Common selections				Other selections				
Length	3/8" Str. fl. x 3/8" Str. fl.	3/8" Str. fl. x FlexFlow™		3/8" fl. x 3/8" 45°	3/8" fl. x 3/8" 90°	3/8" fl. x 1/4" 45°	1/4" fl. x 1/4" 45°	
36"	15636 BC-36"	26036		19636	19836	16236 BCA-36"	20236	
48"	15648 BC-48"	26048		19648	19848	16248 BCA-48"	20248	
60"	15660 BC-60"	26060		19660	19860	16260 BCA-60"	20260	
72"	15672 BC-72"	26072		19672	19872	16272 BCA-72"	20272	
96"	15696 BC-96"	26096		19696	19896	16296 BCA-96"	20296	
10'	15710 BC-120"	26110		19710	19910		20310	
12'	15712 BC-144"	26112		19712	19912	Longer lengths available. Please specify. Longer than 8' not recommended for evacuation.	20312	
25'	15725 BC-300"	26125		19725	19925		20325	
50'	15750 BC-600"	26150		19750	19950		20350	
75'	15775 BC-900"	26175		19775	19975		20375	
100'	15799 BC-1200"	26199		19799	19999		20399	

PLUS II™ 1/2" AND 5/8" HEAVY DUTY COMBINATION CHARGING/VACUUM HOSE

Heavy duty construction with PLUS II™ barrier technology reduces permeation and vacuum loss. Large I.D. reduces vacuum time substantially over 1/4" or 3/8" hose.

- Pull a more complete vacuum
- Faster refrigerant transfer
- Faster charging on large systems
- 3000 psi (207 bar) minimum burst, 600 psi (41 bar) maximum working pressure
- Operating temperature -22° to 176°F (-30° to 80°C)
- Other fittings available on request
- Minimum bend radius: 10" (254 mm)
- **Vacuum rated to 20 microns**
- Made in the USA 



Replacement parts	
UPC#	Description
19015	1/2" and 5/8" Replacement gaskets
19020	1/4" Replacement gasket (10 pak)
19011	3/8" Replacement gasket (10 pak)
19302	"Adjust-a-Valve" opener (10 pak)

Common selections				Other selections			
Length	"C" 1/2" fl. x 1/2" fl.	"D" 5/8" fl. x 5/8" fl.		"CA" 1/4" angle end x 1/2" fl.	"DA" 1/4" angle end x 5/8" fl.	1/2" fl. x 3/8" fl.	3/8" fl. x 3/8" fl.
36"	15836 C-36"	16036 D-36"		16436 CA-36	16636 DA-36	19236	20636
48"	15848 C-48"	16048 D-48"		16448 CA-48	16648 DA-48	19248	20648
60"	15860 C-60"	16060 D-60"		16460 CA-60	16660 DA-60	19260	20660
72"	15872 C-72"	16072 D-72"		16472 CA-72	16672 DA-72	19272	20672
96"	15896 C-96"	16096 D-96"		16496 CA-96	16696 DA-96	19296	20696
10'	15910 C-120"	16110 D-120"				19310	20710
12'	15912 C-144"	16112 D-144"				19312	20712
25'	15925 C-300"	16125 D-300"		36" hose will pull to 20 microns and lower. Hoses longer than 8' not recommended for evacuation.		19325	20725
50'	15950 C-600"	16150 D-600"				19350	20750

Black only. Longer lengths available. Specify type, length and fitting combination.