

REPLACEMENT PARTS FOR PREEVA SERIES

**INDOOR MODELS PDH, SDH, PEH, PXH, AND SHH
OUTDOOR MODELS RDH, REH, RXH, AND RHH**



TABLE OF CONTENTS

MODEL APPLICABILITY 2

REFERENCES 3

SAMPLE RATING PLATES 3

SERIAL NUMBER DECODING 4

ELECTRICAL COMPONENTS 6

BLOWER MOTORS, CONTACTORS, AND STARTERS 24

VENTER COMPONENTS 28

VENT TERMINAL COMPONENTS 31

REPLACEMENT HEAT EXCHANGERS 35

FLUE COLLECTION BOX, BURNER SHIELD, AND CONDENSATE DRAIN ASSEMBLIES 36

BURNER COMPONENTS (MODELS PDH, SDH, RDH, SHH, AND RHH) 38

GAS CONVERSION KITS 39

BLOWER COMPONENTS 39

DRIVE COMPONENTS (PULLEYS AND BELTS) 41

COOLING COIL CABINET COMPONENTS 45

OPTION AR8: ON/OFF DAMPER WITHOUT MIXING BOX 55

INLET DUCT FLANGE, INLET SCREEN, AND REPLACEMENT FILTERS 56

OPTION AS2: INLET AIR HOOD COMPONENTS (MODELS RDH, RHH, RXH, AND REH) 57

MIXING BOX COMPONENTS 58

LOUVER ASSEMBLY COMPONENTS 62

DISCHARGE OPTION COMPONENTS 63

ROOF CURBS 68

CABINET COMPONENTS 74

OPTIONAL EVAPORATIVE COOLING MODULE COMPONENTS 87

IMPORTANT

1. Always include complete model and serial number so that any specification change can be considered for parts replacement. It can save time and expense.
2. In keeping with our policy of continuous product improvement, we reserve the right to alter any information shown here. Specifications are subject to change without notice.
3. We reserve the right to substitute functional replacements.
4. Order by Part Number (PN), not by option designation.

ELECTRICAL COMPONENTS—CONTINUED

Table 3. Electrical Components—Continued

Item No.	Component	Description	Model(s)	PN	Figure Reference
Space-Mounted Thermostats and Controls					
93	Heating/cooling thermostat	Single-stage, 50–90°F, 24V (same as option CL1, Honeywell T812C1000)	All	255350	Figure 9
94		Two-stage, 40–90°F, 24V, electronic non-programmable (same as option CL22, (M/H TH5220D1159)		220630	
95		Electronic two-stage, 7-day programmable, touch screen (same as option CL23, M/H TB8220U1003)		257338	
96		45–88°F, 24 volt, heating/ cooling, 5-2 programmable (same as option CL52, M/H TH411D1007)		220632	
97		Electronic two-stage, 7-day programmable, 24V, switching subbase with auto/cool/off/heat switch and auto/on fan switch (same as option CL33, Honeywell #T7350D1008)		221038	
98	Locking thermostat cover	For items 80–83, height 6-1/2 (165mm) × width 7-1/2 (191 mm) × depth 2-15/16 (75 mm) (same as option CM1)		257464	
		For items 80–84, height 7-1/4 (184 mm) × width 9-3/4 (248 mm) × depth 3-3/8 (86 mm) (same as option CM1B)		257463	
99	Room command module	Sensing space temperature (part of digital control options DG1 and DG2)	—**	211423	
100		Sensing discharge temperature (part of digital control options DG5 and DG6)	All	211424	
101	Room override thermostat	Single-stage (optional part of digital control options DG5 and DG6, same as option CL56)	—**	220631	
102	Wall-mounted space temperature sensor*	Option CL67 (used with options D12B, D12C, D12D, D12E, D12F, and D12G)		—	
103	Remote user interface	Optional (same as option RB2A for use with digital control options D12B, D12C, D12D, D12E, D12F, and D12G)	All	223125	
104	Outside air relative humidity transmitter	Included with all D12 control options		206081	Figure 9
105	Wall-mounted dehumidistat	Same as option CL47 (used with cooling coil with reheat option AU7)		177231	
Optional Remote Console Assemblies (Refer to Table 12 for Dimensions)					
106	Console box***	10-1/16 × 6-5/8 × 2-5/8		107010	
		15-1/16 × 6-5/8 × 2-5/8		107011	
107	Mounting ring	For 10-1/16-inch-long console box		107014	Figure 9
		For 15-1/16-inch-long console box		107015	
108	Indicator light	Red, “BLOWER ON”, “BURNER ON”, “DIRTY FILTER”, quantity = three (3) (Solico 3039-3-11-41610)	All	101889	
109	Switch	SPDT, 15 amps (Cutler Hammer #7505K6)		101901	
110		DPDT, 15 amps (Cutler Hammer #7561K6)		101900	
111	Disconnect switch	Indoor or outdoor		Refer to Table 13	
112	Thermostat	Heating, single-stage		255350	
113		Heating/cooling, single- or two-stage	220630		
114	Potentiometer	Refer to Table 50		16110	
*Part is no longer available. Order replacement PN 260599. This is not a direct replacement. Contact your factory representative or the factory Service Department for wiring instructions.					
**No longer available (may be used on some existing units). If replacement is required, contact your factory representative.					
***Includes mounting ring (item 107) so that the console may be wall-mounted. If the console is to be recessed instead, subtract 5/8-inch from the length and height. The box is of 16 gauge steel with knockout holes for field-wiring. The cover is made of plastic with custom engraving. Order replacement parts for option RC remote console by PN.					